

ANTARES

IP55 PROTECTION FACTOR - ALL INSTALLATIONS

Reference	Volts (V)	Power (W)	Dimensions (mm) - (in)	Weight (kg) - (lb)	Surface T° (°C)	Mini/Max Mounting Height (m)
CASS1100585-51	240	400	600X600X30 - 24X24X1.2	4 - 9	100	2.50/6.00
CASS1100585/208-51	208	400	600X600X30 - 24X24X1.2	4 - 9	100	2.50/6.00
CASS1100585/120-51	120	400	600X600X30 - 24X24X1.2	4 - 9	100	2.50/6.00
CASS1100585-52	240	750	600X1210X30 - 24X48X1.2	8 - 18	100	2.50/6.00
CASS1100585/208-52	208	750	600X1210X30 - 24X48X1.2	8 - 18	100	2.50/6.00
CASS1100585/120-52	120	750	600X1210X30 - 24X48X1.2	8 - 18	100	2.50/6.00
CASS1100585-53	240	1100	600X1820X30 - 24X72X1.2	14 - 31	100	2.50/6.00
CASS1100585/208-53	208	1100	600X1820X30 - 24X72X1.2	14 - 31	100	2.50/6.00
CASS1100510-52	240	1100	1050X1050X30 - 41X41X1.2	12 - 26	100	2.50/6.00
CASS1100510/208-52	208	1100	1050X1050X30 - 41X41X1.2	12 - 26	100	2.50/6.00
CASS1100490-52	240	1200	1000X1200X30 - 39X47X1.2	13 - 29	100	2.50/6.00
CASS1100490/208-52	208	1200	1000X1200X30 - 39X47X1.2	13 - 29	100	2.50/6.00